





YT-1000R



YT-1000L

Model	YT-1000R	YT-1000L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (20~100 psi)	
Stroke	0~90 °	10~150 mm
Impedance	250 Ohm	
Linearity	±1% F.S.	
Hysteresis	±1% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	Ex dm IIB T5, Ex dm IIC T5, Ex dm IIB T6,	
Option	Transmitter or limit Switch	

**Pneumatic-Pneumatic Positioner**



YT-1200L



Model	YT-1200L	YT-1200R
Acting Type	Single Acting or Double Acting	
Input Signal	1.4~7 kgf / cm <sup>3</sup> (3~15 psi)	
Supply pressure	1.4~7 kgf / cm <sup>3</sup> (20~100 psi)	
Stroke	10~150 mm	0~90 °
-		
Linearity	±1% F.S.	±2% F.S.
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	±0.5% F.S.
-		
Option	Transmitter or limit Switch	





**YT-2700**

Model	YT-2700R	YT-2700L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (0.14~0.7 MPa)	
Stroke	0~90 °	5~35 mm
Impedance	Max 460 Ohm / 20 mA DC	
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	Ex ia IIC T6/T5	
Option	HART or +Transmitter	



**YT-3300**



**YT-3300R+L/S**

Model	YT-3300R	YT-3300L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (0.14~0.7 MPa)	
Stroke	0~90 °	20~150 mm
Impedance	Max 460 Ohm / 20 mA DC	
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	Ex ia IIC T6/T5	
Option	HART or +Transmitter or limit Switch	





**YT-2400R**



**YT-2400L**

Model	YT-2400R	YT-2400L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (0.14~0.7 MPa)	
Stroke	0~90 °	10~150 mm
Impedance	Max 430 Ohm / 20 mA DC	
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	ExIIIB (+H <sub>2</sub> ) T6	
Option	HART or +Transmitter or limit Switch	



**YT-2500R**



**YT-2500L**

Model	YT-2500R	YT-2500L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (0.14~0.7 MPa)	
Stroke	0~90 °	10~150 mm
Impedance	Max 460 Ohm / 20 mA DC	
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	Ex ia IIC T6/T5	
Option	HART or +Transmitter or limit Switch	



**YT-2501L (Sensor)**

**YT-2501 (Body)**

Model	YT-2501R	YT-2501L
Acting Type	Single Acting or Double Acting	
Input Signal	4~20mA DC	
Supply pressure	1.4~7 kgf / cm <sup>2</sup> (0.14~0.7 MPa)	
Stroke	0~90 °	10~150 mm
Impedance	Max 460 Ohm / 20 mA DC	
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Explosion Proof type	Ex ia IIC T6/T5	
Option	HART or +Transmitter	



YT-200

YT-205

<b>Mode</b>	<b>YT-205</b>
<b>Max. Output pressure</b>	8.4 kgf / cm <sup>2</sup> (120 psi)
<b>Max. Supply pressure</b>	15 kgf / cm <sup>2</sup> (231 psi)
<b>Ambient Temp.</b>	-20 ~ 70 °C (-4 ~ 158 °F)
<b>Min Filtering size</b>	5 micron

**Volume Booster**



YT-310



YT-315

Model		YT-300 YT-305	YT-310 YT-315	YT-320 YT-325
<b>Max. Supply Pressure</b>		10 kgf/cm <sup>3</sup> (142 psi)		
<b>Max. Signal/Supply Pressure</b>		7 kgf / cm <sup>3</sup> (100 psi)		
<b>Flow Capacity</b>	output	1.02	4.98	2.32
	exhaust	0.86	3.85	1.78
<b>In/ Output Connection</b>		PT (NPT)1/4	NPT 3/4	NPT 1/2
<b>Signal Connection</b>		PT (NPT)1/4		
<b>Linearity</b>		±1% F.S.		
<b>Ambient Temp.</b>		-20 °C ~ 70 °C (-4 ~158 °F)		
<b>Material</b>	YT-300, YT310, YT-320	Aluminum Diecasting		
	YT-305, YT315, YT-325	Stainless Steel 315		



YT-320  
YT-300



YT-325  
YT-305





PTM-5VL



SPTM-5VL

Mode	PTM-5VL SPTM-5VL	PTM-5VR SPTM-5VR
Input type	2 Wire	
Input signal	0 - 30°	0 - 90°
Output signal	4 ~ 20 mA DC	
Load Resistance	0 ~ 600 Ohm / 28V DC	
Supply voltage	9 ~ 28V DC	
Noise Range	50mV p.p	
Conduit	PF 1/2 (G 1/2)	
Enclosure	IP 67	
Explosion Proof	Ex ia IIC T6	
Ambient Temp.	Operating	-30~85°C (-22~185°F)
	Explosion	-20~60°C (-4~140°F)
Linearity	±1% F.S.	
Hysteresis	±0.2% F.S.	
Sensitivity	±0.2% F.S.	

## Limit switch Box



YT-870

YT-875



Model	YT-870M YT-875M	YT-870P YT-875P	YT-870D YT-875D
Switch Type	Mechanical Switch x 2	Proximity Sensor x 2	Mechanical Switch x 4
Switch Rating	AC: 250V 3A, 125V 5A DC: 250V 0.2A, 125V 0.4A, 30V 4A	12-24V DC (Operating voltage: 10-30V DC) P&F Type: 0-25VDC	AC: 125 or 250V 10A, 480V 2A
Enclosure Protection	IP67		
Explosion Proof	Ex d IIC T6		
Ambient Temp.	-20 °C ~ 60 °C		
Conduit Entry	NPT 3/4 (PF3/4, M20)		
Terminal	8 Points		
Mouting Bracket	NAMUR VDI / VDE 3845, ISO 5211		
Material	YT-870	Aluminum Diecasting	
	YT-875	Stainless Steel 315	


**Proses Vana Donanım San. ve Tic. Ltd. Şti.**

Fabrika : Şerifali Mahallesi, Serdivan Sk. No:50, 34775 ÜMRANIYE / İSTANBUL / TURKEY  
Tel : +90 216 - 415 65 40 pbx. Fax : +90 216 - 364 22 52 GSM : 0533 206 13 48 - 49

Mağaza : Necatibey Cd. Serçe Sk. No: 4/A, 34425 KARAKÖY / İSTANBUL / TURKEY  
Tel : +90 212 - 245 77 37/38 Fax : +90 212 - 245 77 39



www.pvd.com.tr e-mail : info@pvd.com.tr