39

40

Seri / Series : T -GM...K

hava *air* · sıcak hava *hot air*

TEKNİK ÖZELLİKLER

- **Gövde :** Pirinç (Ms 58)
- **Çekirdek :** Paslanmaz Çelik
- **Diyafram :** Viton
- **Kovan :** Pirinç (Ms 58) veya Paslanmaz Çelik (AISI 316)
- **Bağlantı :** R Dişli (DIN 2999, ISO R7)
- **Akışkan Sıcaklığı :** Viton (-10 / +160 °C),
- **Ortam Sıcaklığı :** (-20 / +40 °C)
- **Bobin Gücü :** 10 - 14 Watt
- **Soket Koruma Sınıfı :** IP 65
- **Bobin Gerilimi :** 12, 24,42, 48, 110, 220 AC/DC
- **Gerilim Toleransı :** ±%10 V AC/DC
- **Kullanıldığı Yerler :** Hava, Azot

TECHNICAL FEATURES

- ***Body :*** *Brass (Ms 58)*
- ***Plunger :*** *Stainless Steel*
- ***Sealing :*** *Viton*
- ***Tube :*** *Brass (Ms 58) or Stainless Steel (AISI 316)*
- ***Threaded :*** *R Screw (DIN 2999, ISO R7)*
- ***Medium Temperature :*** *Viton (-10 / +160 °C),*
- ***Ambient Temperature :*** *(-20 / +40 °C)*
- ***Power :*** *10 - 14 Watt*
- ***Connector Protection Class :*** *IP 65*
- ***Coil Voltage :*** *12, 24, 42, 48, 110, 220 AC/DC*
- ***Voltage Tolerance :*** *±%10 V AC/DC*
- ***Applications :*** *Air, Nitrogen*

Model	Ölçü *Size*	Orifis *Orifice* (mm)	Kv (m^3/h)	Fark Basınç *Differential Pressure* min. (Bar)	Fark Basınç max..(Bar)	Conta *Seal*	Resim *Picture*	Açıklama *Description*
T - GM 102.K	G 3/8"	12.5	2.6	0,5	16	Viton	39	Pilot Kontrollu Diyaframlı *Pilot Operated with Diaphragm*
T - GM 102 KA					16			
T - GM 102 K1					40			
T - GM 102 K1A					40			
T - GM 103.K	G 1/2"	14.5	3.5	0,5	16			
T - GM 103.KA					16			
T - GM 103.K1					40			
T - GM 103.K1A					40			
T - GM 104.K	G 3/4"	17	4.2	0,5	16			
T - GM 104.KA					16			
T - GM 104.K1					40			
T - GM 104.K1A					40			
T - GM 105.K	G 1"	17	4.2	0,5	16	Viton	40	
T - GM 105.KA					16			
T - GM 105.K1					40			
T - GM 105.K1A					40			

A: Normalde Açık / *Normally Open*