Seri / Series T-YA - 400

yağ *oil* · kimyasal malz. *chemicals*

34

35

36

37

38

TEKNİK ÖZELLİKLER

- **Gövde :** Pirinç (Ms 58)
- **Çekirdek :** Paslanmaz Çelik
- **Diyafram :** Viton
- **Kovan :** Paslanmaz Çelik (AISI 316)
- **Bağlantı :** R Dişli (DIN 2999, ISO R7)
- **Akışkan Sıcaklığı:** Viton (-10 / +160 °C),
- **Ortam Sıcaklığı :** (-20 / +40 °C)
- **Bobin Gücü :** 10 - 14 Watt
- **Soket Koruma Sınıfı :** IP 65
- **Bobin Gerilimi :** 12, 24,42, 48, 110, 220 AC/DC
- **Gerilim Toleransı :** ±%10 V AC/DC
- **Kullanıldığı Yerler :** Fuel Oil ,Yağ

TECHNICAL FEATURES

- ***Body :*** *Brass (Ms 58)*
- ***Plunger :*** *Stainless Steel*
- ***Sealing :*** *Viton*
- ***Tube :*** *Stainless Steel (AISI 316)*
- ***Threaded :*** *R Screw (DIN 2999, ISO R7)*
- ***Medium Temperature:*** *Viton (-10 / +160 °C),*
- ***Ambient Temperature :*** *(-20 / +40 °C)*
- ***Power :*** *10 - 14 Watt*
- ***Connector Protection Class :*** *IP 65*
- ***Coil Voltage :*** *12, 24, 42, 48, 110, 220 AC/DC*
- ***Voltage Tolerance :*** *±%10 V AC/DC*
- ***Applications :*** *for Fuel oil, Hydraulic Oil*

Model	Ölçü *Size*	Orifis *Orifice* (mm)	Kv (m^3/h)	Fark Basınç *Differential Pressure* min. (Bar)	Fark Basınç max..(Bar)	Conta *Seal*	Resim *Picture*	Açıklama *Description*
T - YA 400	G 1/8"	2.5	0.29	0	30	RUBY	34	Direkt Çekmeli *Direct Operated*
T - YA 400.A		3.2		0	30		34	
T - YA 401	G 1/4"	2.5	0.29	0	30		34	
T - YA 401.A		3.2		0	30		34	
T - YA 402	G 3/8"	12.5	2.6	0.5	16	Viton	35	Pilot Kontrollu Diyaframlı *Pilot Operated with Diaphragm*
T - YA 402.A					16		36	
T - YA 402.1					40		35	
T - YA 402.1A					40		36	
T - YA 403	G 1/2"	14.5	3.5	0.5	16		35	
T - YA 403.A					16		36	
T - YA 403.1					40		35	
T - YA 403.1A					40		36	
T - YA 404	G 3/4"	17	4.2	0.5	16		35	
T - YA 404.A					16		36	
T - YA 404.1					40		35	
T - YA 404.1A					40		36	
T - YA 405	G 1"	17	4.3	0.5	16		37	
T - YA 405.A					16		38	
T - YA 405.1					40		37	
T - YA 405.1A					40		38	
T - YA 409	G 1 1/4"	32	14	0.5	10		22	
T - YA 409A					10		23	
T - YA 406	G 1 1/2"	40	22	0.5	10		22	
T - YA 406A					10		23	
T - YA 407	G 2"	50	40	0.5	10		22	
T - YA 407A					10		23	
T - YA 408.8	G 1/8"-3/2	2.5	0.09	0.5	25	RUBY	34	Direkt Çekmeli *Direct Operated*
T - YA 408.4	G 1/4"-3/2	2.5			25		34	

A: Normalde Açık / *Normally Open*
T: Tepeden Girişli / *Input from top*